



S5426 5.4GHz 26dBi Solid Parabolic Antenna

Datasheet: 071505



Main Features:

- Excellent front-to-back ratio and narrow beam-width to reduce interference
- Simple to install and aim
- Corrosion resistant spun aluminium alloy reflector
- Durable vented, solid brass feed
- Supplied with stainless steel and aluminium mounting hardware.
- Designed & manufactured in Australia



Electrical Specifications:

Frequency	5470 - 5725MHz
Minimum gain	26dBi
Vertical beam-width	6°
Horizontal beam-width	7°
Front-to-back ratio	-40dB
Impedance	50 Ohms
Maximum power	10 Watts
Polarization	Vertical or horizontal
VSWR	<1:1.5



Mechanical Specifications:

Standard connector	N-Female
Reflector aperture	520mm diameter
Elevation range	40°
Azimuth range	360°
Mass	1.8kg
Mast diameter	30mm - 60mm
Operating temperature	-20°C to 70°C
Standards compliance	AS1471 & MIL-C81706
Wind load at 200kmph	75kg
Wind survival speed	200kmph

Pacific Satellite Pty Ltd
12 George Rd
Salamander Bay, NSW 231
AUSTRALIA

antennas that go the distance

Phone: +61 2 4982 0855

Fax: +61 2 4982 0566

www.pacsat.com.au

E-mail: sales@pacsat.com.au