



# SEC5813/180 5.8GHz 13dBi 180° Sector Antenna

Data Sheet 300401

## Main Features


- Focuses radiated energy into required sector
- Compact, low profile antenna
- Suitable for indoor and outdoor use
- Heavy duty aluminium construction with fibreglass radome
- Supplied complete with stainless steel hardware for surface and mast/tower mounting
- Vertically polarized
- Optional tilt-kit available
- Designed & manufactured in Australia




## Electrical Specifications

Frequency	5725 - 5875MHz
Antenna type	Collinear
Minimum gain	13dBi
Electronic beam-tilt	-1°
Vertical beam-width	5°
Horizontal beam-width	180°
Return loss	-18±3dB
Impedance	50 Ohms
Maximum power	20 Watts
Standard polarization	Vertical
VSWR	<1:1.5

## Typical Radiation Patterns



Vertical Plane



Horizontal Plane

## Mechanical Specifications

Standard connector	N-Female
Mass	1kg
Length	500mm
Mast diameter	30mm - 60mm
Survival wind rating	300kmph
Wind loading	13kg at 200kmph
Operating temperature	-20°C to 70°C
Standards compliance	AS1471

Pacific Satellite Pty Ltd  
12 George Road, PO Box 100  
Salamander Bay, NSW 2317  
AUSTRALIA

antennas that go the distance



National Sales: 1800 001 081  
Phone: 61 2 4982 0855  
Fax: 61 2 4982 0566  
[www.pacsat.com.au](http://www.pacsat.com.au)  
[sales@pacsat.com.au](mailto:sales@pacsat.com.au)