



GAO916 915MHz 16dBi Grid Antenna

Data Sheet 050808

Main Features

- Simple to install and aim
- Low mast and wind loading
- Surface-treated, corrosion resistant aluminium alloy grid reflector
- Vented, weatherproof feed housing
- Durable solid brass feed (not PCB)
- Good multi-path interference rejection
- Excellent front to back ratio
- Supplied with mounting hardware for attaching to mast or tower member
- Designed & manufactured in Australia
- 24-month warranty
- Stainless steel/aluminium mounting hardware is optional



Electrical Specifications

Frequency	900 – 930MHz
Minimum gain	16dBi
Vertical beam-width	22°
Horizontal beam-width	18°
Front-to-back ratio	30dB
Impedance	50 Ohms
Maximum power	10 Watts
Polarization	Vertical or horizontal
VSWR	<1:1.5

Mechanical Specifications

Standard connector	N-Male (others available on request)
Cable tail	500mm
Reflector aperture	900mm x 600mm
Elevation range	25°
Azimuth range	360°
Mass	3kg
Mast diameter	30mm - 60mm
Operating temperature	-20°C to 70°C
Standards compliance	AS1471 & MIL-C81706
Wind load at 100kmph	20kg

Pacific Satellite Pty Ltd
12 George Road, PO Box 100
Salamander Bay, NSW 2317
AUSTRALIA

antennas that go the distance



National Sales: 1800 001 081
Phone: 61 2 4982 0855
Fax: 61 2 4982 0566
www.pacsat.com.au
sales@pacsat.com.au