



GA5433 5.4GHz 33dBi Parabolic Grid Antenna

Datasheet: 090302

Main Features:

- Robust construction
- Low mast and wind loading
- Surface-treated, corrosion resistant aluminium alloy grid reflector
- Durable solid brass feed
- Excellent front-to-back ratio
- Supplied with mounting hardware for attaching to mast or tower member – screw adjustable in azimuth & elevation
- Designed & manufactured in Australia



Electrical Specifications:

Frequency	5460 - 5875MHz
Minimum gain	33dBi, 5.8GHz 32dBi, 5.4GHz
Vertical beam-width	6°
Horizontal beam-width	4°
Front-to-back ratio	40dB
Impedance	50 Ohms
Maximum power	10 Watts
Polarization	Vertical or horizontal

Mechanical Specifications:

Standard connector	N-Female
Reflector aperture	1200mm x 900mm
Elevation range	±20°
Azimuth range	360°
Mass	10kg
Mast diameter	25mm - 60mm
Operating temperature	-20°C to 70°C
Standards compliance	AS1471 & MIL-C81706
Wind load at 100kmph	50kg
Wind Load at 200kmph	210kg

Pacific Satellite Pty Ltd
12 George Rd
Salamander Bay, NSW 231
AUSTRALIA

antennas that go the distance

Phone: +61 2 4982 0855

Fax: +61 2 4982 0566

www.pacsat.com.au

E-mail: sales@pacsat.com.au