



## OMN1007 2.4GHz 7dBi Omni Antenna

Data Sheet 051709

### Main Features


- High-quality, 7dBi omni-directional base station antenna
- Collinear construction for excellent horizontal circularity/null-free coverage
- Ideally suited for use with bi-directional amplifiers to achieve EIRP levels
- Rugged aluminium and fibreglass construction
- Vertically polarised
- Stainless steel mounting hardware included
- Mount allows adjustment in two dimensions (see picture)
- Designed & manufactured in Australia
- 24-month warranty



### Electrical Specifications

Frequency	2400 - 2500MHz
Antenna type	Collinear
Minimum gain	7dBi
Electronic beam-tilt	-1°
Vertical beam-width	16°
Horizontal beam-width	360° ± 0.5dB
Return loss	20dB
Impedance	50 Ohms
Maximum power	200 Watts
Standard polarization	Vertical
VSWR	<1:1.5

### Typical Radiation Pattern



### Mechanical Specifications

Standard connector	N-Female
Mass	1kg
Length	900mm
Radome diameter	35mm
Mast diameter	30mm - 60mm
Survival wind rating	220kmph
Wind loading	5kg at 200kmph
Operating temperature	-20°C to 70°C
Standards compliance	AS1471

Pacific Satellite Pty Ltd  
12 George Road, PO Box 100  
Salamander Bay, NSW 2317  
AUSTRALIA

antennas that go the distance



National Sales: 1800 001 081  
Phone: 61 2 4982 0855  
Fax: 61 2 4982 0566  
[www.pacsat.com.au](http://www.pacsat.com.au)  
[sales@pacsat.com.au](mailto:sales@pacsat.com.au)