



P5423 5GHz 23dBi Patch Antenna

Data Sheet 092104

Main Features

- Low profile and unobtrusive appearance
- Wide operating bandwidth
- Low side and back lobes
- Easy to install
- Minimal depth
- Suitable for indoor and outdoor use
- Supplied with mounting bracket



Electrical Specifications

Frequency	5150 - 5850MHz
Minimum gain	23dBi
Vertical beam-width	9°
Horizontal beam-width	9°
VSWR	<1.7:1
Front-to-back ratio	>-32dB
Cross-polar rejection	>-20dB
Impedance	50 Ohms
Maximum input power	6 Watts
Polarisation	Vertical/Horizontal

Mechanical Specifications

Standard connector	N-Female
Dimensions	300mm x 300mm
Depth	25mm
Radome material	White polycarbonate
Lightning protection	DC grounded
Base plate	Aluminium
Weight	1.2Kg
Operating temperature	-20°C to 70°C
Survival wind speed	220kmph

Pacific Satellite Pty Ltd
12 George Road, PO Box 100
Salamander Bay, NSW 2317
AUSTRALIA

antennas that go the distance



National Sales: 1800 001 081
Phone: 61 2 4982 0855
Fax: 61 2 4982 0566
www.pacsat.com.au
sales@pacsat.com.au