



S5421 5.4GHz 21dBi Solid Parabolic Antenna

Datasheet: 071505

Main Features:


- Excellent front-to-back ratio and narrow beam-width to reduce interference
- Simple to install and aim
- Corrosion resistant spun aluminium alloy reflector
- Supplied with stainless steel and aluminium mounting hardware.
- Designed & manufactured in Australia



Electrical Specifications:

Frequency	5470 - 5875MHz
Minimum gain	21dBi, 5.8GHz 20dBi, 5.4GHz
Vertical beam-width	13°
Horizontal beam-width	13°
Front-to-back ratio	-40dB
Impedance	50 Ohms
Maximum power	10 Watts
Polarization	Vertical or horizontal


Horizontal Radiation Pattern



Mechanical Specifications:

Standard connector	N-Female
Reflector aperture	320mm diameter
Elevation range	40°
Azimuth range	360°
Mass	1.8kg
Mast diameter	30mm - 60mm
Operating temperature	-20°C to 70°C
Standards compliance	AS1471 & MIL-C81706
Wind load at 200kmph	28kg
Wind survival speed	200kmph
Operating temperature	-40°C to 65°C

Vertical Radiation Pattern



Pacific Satellite Pty Ltd
12 George Rd
Salamander Bay, NSW 231
AUSTRALIA

antennas that go the distance

Phone: +61 2 4982 0855
Fax: +61 2 4982 0566
www.pacsat.com.au
E-mail: sales@pacsat.com.au