

SEC3510/90 3.5GHz 11dBi 90° Sector Antenna

Data Sheet 051709

Main Features

- Focuses radiated energy into 90 degree sector
- Reduces congestion/interference from outside the sector
- Compact, low profile antenna
- Suitable for indoor and outdoor use
- Heavy duty aluminium construction with fibreglass radome
- Supplied complete with stainless steel hardware for surface and mast/tower mounting
- Optional tilt-kit available
- Vertically polarized
- Designed & manufactured in Australia
- 24-month warranty




Electrical Specifications

Frequency	3400 - 3600MHz
Antenna type	Collinear
Minimum gain	11dBi
Electronic beam-tilt	-1°
Vertical beam-width	8°
Horizontal beam-width	90°
Return loss	18±3dB
Impedance	50 Ohms
Maximum power	200 Watts
Standard polarization	Vertical
VSWR	<1:1.5


Mechanical Specifications

Standard connector	N-Female
Mass	2kg
Length	660mm
Mast diameter	30mm - 60mm
Survival wind rating	300kmph
Wind loading	10kg at 200kmph
Operating temperature	-20°C to 70°C
Standards compliance	AS1471
Wind load at 100kmph	3kg

Typical Radiation Patterns



Vertical Plane



Horizontal Plane

Pacific Satellite Pty Ltd
12 George Road, PO Box 100
Salamander Bay, NSW 2317
AUSTRALIA



National Sales: 1800 001 081
Phone: 61 2 4982 0855
Fax: 61 2 4982 0566
www.pacsat.com.au
sales@pacsat.com.au

ERROR: undefined
OFFENDING COMMAND: f'~

STACK: