



SEC3513/120 3.5GHz 13dBi 120° Sector Antenna

Data Sheet 051709

Main Features



- Focuses radiated energy into 120 degree sector
- Reduces congestion/interference from outside the sector
- Compact, low profile antenna
- Suitable for indoor and outdoor use
- Heavy duty aluminium construction with fibreglass radome
- Supplied complete with stainless steel hardware for surface and mast/tower mounting
- Optional tilt-kit available
- Vertically polarized
- Designed & manufactured in Australia
- 24-month warranty



Electrical Specifications

Frequency	3400 - 3600MHz
Antenna type	Collinear
Minimum gain	13dBi
Electronic beam-tilt	-1°
Vertical beam-width	4.5°
Horizontal beam-width	120°
Return loss	18±3dB
Impedance	50 Ohms
Maximum power	200 Watts
Standard polarization	Vertical
VSWR	<1:1.5

Typical Radiation Patterns



Mechanical Specifications

Standard connector	N-Female
Mass	2kg
Length	830mm
Mast diameter	30mm - 60mm
Survival wind rating	300kmph
Wind loading	14kg at 200kmph
Operating temperature	-20°C to 70°C
Standards compliance	AS1471
Wind load at 100kmph	4kg

Pacific Satellite Pty Ltd
12 George Road, PO Box 100
Salamander Bay, NSW 2317
AUSTRALIA

antennas that go the distance

National Sales: 1800 001 081
Phone: 61 2 4982 0855
Fax: 61 2 4982 0566
www.pacsat.com.au
sales@pacsat.com.au